

RANGE	CODE	MODEL	FUNCTION
Refrigerated Counters	MACROOOO34O	TRTIPBTSP	Refrigerated Counters MI

ITEM

Refrigerated counter MI 1 door -10-20°C without top



RANGE                      CODE                      MODEL                      FUNCTION  
**Refrigerated Counters**   **MACROOOO340**   **TRTIPBTSP**   **Refrigerated Counters MI**

ITEM

**Refrigerated counter MI I door -10-20°C without top**



#### TECHNICAL SPECIFICATIONS

RANGE:	<b>-20/-10°C</b>	
WIDTH (mm):	<b>903</b>	
DEPTH (mm):	<b>680</b>	
HEIGHT (mm):	<b>850</b>	
WEIGHT (Kg):	<b>132</b>	
VOLUME (m <sup>3</sup> ):	<b>0.54</b>	
EL. POWER (kW):	<b>0.5</b>	
VOLTAGE:	<b>VAC230</b>	
FREQUENCY (Hz):	<b>50Hz</b>	
INTERNAL DIM. (mm):	<b>343x530x580(h) mm</b>	
EXTERNAL MATERIAL:	<b>304</b>	
INTERNAL MATERIAL:	<b>304</b>	
GROSS CAPACITY (L):	<b>105</b>	
OPERATING MODE:	<b>Ventilated</b>	
DOORS:	<b>1 Door</b>	
STANDARD EQUIPMENT:	<b>1 Plastic-coated grid GNI/I for each door.</b>	
DEFROST TYPE:	<b>Hot gas</b>	
REFRIGERANT POWER:	<b>520</b>	
ENERGY CLASS:	<b>E</b>	GAS TYPE: <b>R290 / 3</b>
REFRIGERANT QUANTITY (g):	<b>120</b>	
NOISE LEVEL:	<b>53</b>	
ENERGY PER YEAR:	<b>2390</b>	
CLIMATE CLASS:	<b>5 +40°C 40%</b>	

#### DESCRIPTION


Single-shell structure H=710mm, in stainless steel AISI 304. Without top. External scotch-brite satin finish. 60mm insulation thickness for the casing and 50mm for the doors with high density foam (40 kg/mc). External back plate in galvanized steel, as option in stainless steel AISI 304 scotch-brite. Feet in stainless steel adjustable in height H 140/230mm. Cell with rounded corners for a more effective internal cleaning. Self-closing doors with safety stop at 95°. Easily removable door and drawers magnetic gaskets. Monobloc refrigerating unit. Ducted ventilation system on the back for a perfect and homogeneous internal temperature. Hot gas defrost and automatic evaporation of condensation water. Ergonomic handles. Both versions available on request with the technical compartment on the left. Standard power supply 230V/50H. Upper and lower door hinges fixed frontally to the frame (replaceable with no need to remove the worktop). Reversible doors. Equipped with 1 set of runners + 1 GN I/I plastic-coated steel grid. Refrigerant gas R290. Energy Efficiency class E (2390 kWh/year)



RANGE	CODE	MODEL	FUNCTION
Refrigerated Counters	MACROOOO34O	TRTIPBTSP	Refrigerated Counters MI

ITEM

Refrigerated counter MI I door -10-20°C without top



**INSTALLATION SPECIFICATIONS**

(E) Electrical Connection:

VAC230 50Hz

Type of electrical plug:

with Schuko plug and cable

