

RANGE

Self-Service 700

CODE

CRO787370

MODEL

SPEAR715

FUNCTION

Refrigerated units

ITEM

Refrigerated display and 4 GN1/I refrigerated top on refrigerated cupboard



RANGE	CODE	MODEL	FUNCTION
Self-Service 700	CRO787370	SPEAR715	Refrigerated units

ITEM

Refrigerated display and 4 GN I/I refrigerated top on refrigerated cupboard



TECHNICAL SPECIFICATIONS

WIDTH (mm):	1500
DEPTH (mm):	700
HEIGHT (mm):	1700
WEIGHT (Kg):	250
VOLUME (m ³):	2.5
EL. POWER (kW):	1.25
GAS TYPE:	R455a

DESCRIPTION

Display unit with refrigerated top, depth 30 mm. , capacity 4 GN I/I containers H=20 mm. Exchangers and ventilation in the upper part to facilitate air circulation. Sliding glass doors on operator side, Plexiglas swing hatched on customer side. Stainless steel grille shelves, easily removed for cleaning, can be positioned at two different heights. Led lighting. Temperature range: +4 / +15°C, temperature adjusted using a digital electronic thermostat. Refrigerant gas R455a. Ventilated cold storage, 2 GN I/I compartments with grille or container holders. Thermal insulation in high-density polyurethane Refrigerating unit with air condensation. Digital electronic thermostatic control, 1 per shelf and 1 per cold storage, adjustable to 0 a +8°C, luminous main switch. Cold storage humidity control, automatic defrosting control. AISI 304 stainless steel structure. Top with rounded edges, 12/10 thick, height 50 mm. Internal compartment with radiused corners for easy cleaning. Stainless steel leveling feet. Supplied with front panels.

