

RANGE	CODE	MODEL	FUNCTION
MI - IIO	MAMCOOIII80	CIII4EG	Induction Ranges

ITEM

Pass through 2 zone induction top on open stand



RANGE	CODE	MODEL	FUNCTION
MI - 110	MAMCOO11180	C1114EG	Induction Ranges

ITEM

Pass through 2 zone induction top on open stand



TECHNICAL SPECIFICATIONS

WIDTH (mm):	400
DEPTH (mm):	1100
HEIGHT (mm):	900
WEIGHT (Kg):	64
VOLUME (m ³):	0.5
EL. POWER (kW):	10
VOLTAGE:	VAC400 3N
INTERNAL BASE UNIT DIM. (mm):	340x1000x390(h)
COOKING ZONES N°:	2
COOKING ZONES DIM. (mm):	Ø 280 mm
COOKING ZONE DETAILS:	2 x 5 kW
IP GRADE:	IPX5

DESCRIPTION

Pass-through freestanding induction boiling top, on open cabinet base, in AISI 304 stainless steel. 20/10 pressed steel top with anti-spill front edge, designed for flush alignment with hermetic seal supplied. 6 mm thick glass ceramic cooking surface hermetically sealed to the top and designed to create 2 independent cooking zones, each with underlying 5 kW Ø 280 mm round inductors. Pan detection system that activates heating when cooking receptacle is present. The cooking zones are identified by screen printed markings and equipped with residual heat indicators. IO-position energy selector for heat control with shape designed to prevent water infiltration, equipped with integral indicator lights for instant recognition of heating and correct operation of the appliance. Integral power-box complete with main safety sensor. IPX5 water-resistant rating. Appliance equipped with stainless steel adjustable feet.

